

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

FILE NO.: 72201 TRANSDUCER SPRAY.doc

MSDS DATE: 4/4/2011

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ANTI-FOULANT TRANSDUCER SPRAY

SYNONYMS:

PRODUCT CODES: 72201

MANUFACTURER: Flexabar Corporation

DIVISION:

ADDRESS:

EMERGENCY PHONE: 1-800-424-9300

CHEMTREC PHONE: 1-800-424-9300

OTHER CALLS: 1-732-901-6500

FAX PHONE: 1-732-901-6504

CHEMICAL NAME: NA

CHEMICAL FAMILY: NA

CHEMICAL FORMULA: NA

PRODUCT USE: ANTI-FOULANT TOP COAT FOR TRANSDUCERS

PREPARED BY: Hamdi Latif

SECTION 1 NOTES:

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT: ACETONE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
67-54-1	11.00 – 16.00 <u>ppm</u>	<u>mg/m3</u>	NO
OSHA PEL-TWA:			
OSHA PEL STEL :	1000.00 PPM		
OSHA PEL CEILING:			
ACGIH TLV-TWA:	500.00 PPM		
ACGIH TLV STEL:	750.00 PPM		
ACGIH TLV CEILING:			

INGREDIENT: Acrylic Copolymer

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
Proprietary	11.00 – 19.00		NO
	<u>ppm</u>	<u>mg/m3</u>	
OSHA PEL-TWA:	NONE		
OSHA PEL STEL :	NONE		
OSHA PEL CEILING:	NONE		
ACGIH TLV-TWA:	NONE		
ACGIH TLV STEL:	NONE		
ACGIH TLV CEILING:	NONE		

INGREDIENT: METHYL ETHYL KETONE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
78-93-3	11.00 – 16.00 <u>ppm</u>	<u>mg/m3</u>	YES
OSHA PEL-TWA:	200.00		
OSHA PEL STEL :	300.00		
OSHA PEL CEILING:			
ACGIH TLV-TWA:	200.00		
ACGIH TLV STEL:	300.00		
ACGIH TLV CEILING:			

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

FILE NO.: 72201 TRANSDUCER SPRAY.doc

MSDS DATE: 4/4/2011

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS - CONTINUED

INGREDIENT: XYLENE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
1330-20-7	8.00 – 12.00 <u>ppm</u>	<u>mg/m3</u>	YES
OSHA PEL-TWA: OSHA PEL STEL : OSHA PEL CEILING:	100.00 PPM		
ACGIH TLV-TWA: ACGIH TLV STEL: ACGIH TLV CEILING:			

INGREDIENT: TOLUENE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
108-88-3	8.00 – 12.00 <u>ppm</u>	<3 <u>mg/m3</u>	YES
OSHA PEL-TWA: OSHA PEL STEL : OSHA PEL CEILING:	200		
ACGIH TLV-TWA: ACGIH TLV STEL: ACGIH TLV CEILING:	50		

INGREDIENT: COPPER THIOCYANATE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
1111-67-7	5.00 – 8.00 <u>ppm</u>	<u>mg/m3</u>	YES
OSHA PEL-TWA: OSHA PEL STEL : OSHA PEL CEILING:			
ACGIH TLV-TWA: ACGIH TLV STEL: ACGIH TLV CEILING:		NO DATA AVAILABLE	

INGREDIENT: METHYL ISOBUTYL KETONE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
108-10-1	3.00 – 10.00 <u>ppm</u>	<u>mg/m3</u>	YES
OSHA PEL-TWA: OSHA PEL STEL : OSHA PEL CEILING:	50 75	205 300	
ACGIH TLV-TWA: ACGIH TLV STEL: ACGIH TLV CEILING:	50 75	205 307	

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

FILE NO.: 72201 TRANSDUCER SPRAY.doc

MSDS DATE: 4/4/2011

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS - CONTINUED

INGREDIENT: POLYTETRAFLUOROETHYLENE

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
9002-84-0	3.00 – 6.80		NO
	<u>ppm</u>	<u>mg/m3</u>	
OSHA PEL-TWA:		10 total dust	
OSHA PEL STEL :		5 respirable dust	
OSHA PEL CEILING:			
ACGIH TLV-TWA:			
ACGIH TLV STEL:			
ACGIH TLV CEILING:			

INGREDIENT: n - Butane

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
106-97-8	9.0 – 14.0		NO
	<u>ppm</u>	<u>mg/m3</u>	
OSHA PEL-TWA:			
OSHA PEL STEL :			
OSHA PEL CEILING:			
ACGIH TLV-TWA:	1000		
ACGIH TLV STEL:			
ACGIH TLV CEILING:			

INGREDIENT: Propane

<u>CAS NO.</u>	<u>% WT</u>	<u>% VOL</u>	<u>SARA 313 REPORTABLE</u>
108-65-6	9.0 – 14.0		NO
	<u>ppm</u>	<u>mg/m3</u>	
OSHA PEL-TWA:			
OSHA PEL STEL :			
OSHA PEL CEILING:			
ACGIH TLV-TWA:	1000		
ACGIH TLV STEL:			
ACGIH TLV CEILING:			

SECTION 2 NOTES:

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Warning! Flammable liquid and vapor.
Color: Clear, White, Gray or Black Form: Liquid Odor: Sweet, Ester

Overexposure may cause nervous system effects. May cause serious disturbances of heart rhythm. May cause skin irritation. Causes eye irritation. Causes respiratory tract irritation. Harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage

ROUTES OF ENTRY:.....: skin contact from liquid and aerosols (spray application). Inhalation.

POTENTIAL HEALTH EFFECTS:

EYES:

ACUTE EYE CONTACT...Liquid, aerosols or vapors are irritating and can cause tearing, reddening and swelling. If left untreated, corneal damage can occur and is slow to heal. However damage is usually reversible. See first aid measures for treatment.

CHRONIC EYE CONTACT...None Found

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

FILE NO.: 72201 TRANSDUCER SPRAY.doc

MSDS DATE: 4/4/2011

SECTION 3: HAZARDS IDENTIFICATION - CONTINUED

SKIN: May be absorbed through the skin in harmful amounts. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash) Prolonged or repeated skin contact may cause irritation.

INGESTION: Moderately toxic. Irritating to mouth, throat, and stomach. May produce central nervous system effects, which may include dizziness, loss of balance and coordination, unconsciousness, coma and even death? Product may be harmful or fatal if swallowed. Pulmonary aspiration hazard. After ingestion may enter lungs and produce damage.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, loss of consciousness and even death). Repeated overexposure can cause a hearing loss in laboratory animals. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Solvent "huffing/snuffing" (abuse) or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage, serious disturbances of heart rhythm and sudden death. Prolonged or repeated exposure may cause liver and kidney damage.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

The following diseases or disorders may be aggravated by exposure to this product: skin, eye, liver, kidney, nervous system, respiratory system, lung (asthma-like conditions)

CARCINOGENICITY

OSHA: Not Listed	ACGIH: Not Listed	NTP: Not Listed	IARC: Not Listed
OTHER:			

SECTION 3 NOTES:

Xylene and all components thereof are listed on ACGIH

Benzene is listed on the OSHA List of Regulated Carcinogens and The OSHA List of Select Carcinogens also on the NTP List and the IARC Group 1 list.

Ethyl Benzene is listed on The IARC Group 3 list

SECTION 4: FIRST AID MEASURES

EYES: Flush with copious amounts of water (warm if possible) for at least 15 minutes, holding eyelids open at all times. Refer to a physician or ophthalmologist for immediate follow-up.

SKIN: Remove all contaminated clothing. Wash affected skin thoroughly with soap and water. Wash contaminated clothing thoroughly with soap and water before reuse. See physician if irritation develops or persists after washing.

INGESTION: DO NOT INDUCE VOMITING. Do not give liquids. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

INHALATION: Move to an area free from further exposure. If not breathing administer artificial respiration as needed. If breathing is difficult give oxygen and monitor. Seek immediate medical attention. Asthmatic – type symptoms may develop and may be immediate or delayed for several hours. Consult a physician should this occur.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 4 NOTES:

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 6.6
(% BY VOLUME) **XYLENE**
LOWER: 1.1

FLASH POINT:

F: -156 (Butane)

C:

METHOD USED: Open Cup

AUTOIGNITION TEMPERATURE:

MATERIAL SAFETY DATA SHEET

FILE NO.: 72201 TRANSDUCER SPRAY.doc

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

MSDS DATE: 4/4/2011

EYE PROTECTION: Liquid chemical goggles. If contact lenses are worn vapor resistant goggles should be worn. If a splash hazard exists chemical goggles should be used in conjunction with a full face shield.

SKIN PROTECTION: Chemical/solvent resistant gloves.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Where splashing is possible full chemical protective clothing should be worn,.

WORK HYGIENIC PRACTICES: Safety showers and eyewash stations should be available. Wash promptly after working with this Product. Remove and wash or dispose of all contaminated clothing and or equipment. Follow all label Precautions.

SECTION 8 NOTES:

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, White Gray or Black Liquid

ODOR: Sweet Ester

PHYSICAL STATE: liquid

pH AS SUPPLIED: NA

pH (Other): NA

BOILING POINT:

F: NE

C: NE

MELTING POINT:

F: NE

C: NE

FREEZING POINT:

F: NE

C: NE

VAPOR PRESSURE (mmHg): NE

@

F:

C:

VAPOR DENSITY (AIR = 1): NE

@

F:

C:

SPECIFIC GRAVITY (H2O = 1):

@ .92

F: 77

C:

EVAPORATION RATE: NE MIXTURE

BASIS (=1):

SOLUBILITY IN WATER: Insoluble

SECTION 9 NOTES:

MIXTURE

SECTION 10: STABILITY AND REACTIVITY

STABLE

UNSTABLE

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY):

INCOMPATIBILITY (MATERIAL TO AVOID): Contact with amines, strong oxidizing agents, alcohols, bases or halogenated materials.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Dioxide, Carbon Monoxide and oxides of Nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

MATERIAL SAFETY DATA SHEET

FILE NO.: 72201 TRANSDUCER SPRAY.doc

NAME OF PRODUCT ANTI-FOULING TRANSDUCER SPRAY

MSDS DATE: 4/4/2011

CONDITIONS TO AVOID (POLYMERIZATION): Will not Polymerize.

SECTION 10 NOTES:

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

SECTION 11 NOTES:

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Data Available

SECTION 12 NOTES:

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste must be disposed of in accordance with federal, state and local environmental control regulations. This product contains components that are RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service. Empty containers must be handled with care due to product residue.

RCRA HAZARD CLASS:

SECTION 13 NOTES:

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: FLAMMABLE GAS (AEROSOL), 2
HAZARD CLASS: 3
ID NUMBER: UN 1950
PACKING GROUP: II
LABEL STATEMENT: Flammable Gas

WATER TRANSPORTATION

PROPER SHIPPING NAME: FLAMMABLE GAS (AEROSOL), 2
HAZARD CLASS: 3
ID NUMBER: UN 1950
PACKING GROUP: III
LABEL STATEMENTS: Flammable Gas

AIR TRANSPORTATION

PROPER SHIPPING NAME: FLAMMABLE GAS (AEROSOL), 2
HAZARD CLASS: 3
ID NUMBER: UN 1950
PACKING GROUP: II
LABEL STATEMENTS: Flammable Gas

OTHER AGENCIES:

SECTION 14 NOTES:

MATERIAL SAFETY DATA SHEET
NAME OF PRODUCT **ANTI-FOULING TRANSDUCER SPRAY**

FILE NO.: 72201 TRANSDUCER SPRAY.doc
MSDS DATE: 4/4/2011

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All components of this product are listed.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Not Listed

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): Not Listed

311/312 HAZARD CATEGORIES: FLAMMABLE LIQUID

313 REPORTABLE INGREDIENTS:	XYLENE	CAS # 133-20-7
METHYL	ISOBUTYL KETONE	CAS # 108-10-1
TOLUENE	CA	S #108-88-3
METHYL	ETHYL KETONE	CAS #1111-67-7

STATE REGULATIONS:

INTERNATIONAL REGULATIONS:

SECTION 15 NOTES:

SECTION 16: OTHER INFORMATION

ABBREVIATIONS: ACGIH = American Conference of Governmental Industrial Hygienists
OSHA = Occupational Safety and Health Administration
TLV = Threshold Limit Value
TWA = Time Weighted Average
PEL = Permissible Exposure Limit
STEL = Short Term Exposure Limit
NA = Not Applicable
NE = Not Established

PREPARATION INFORMATION: HMIS Hazard Ratings Scale 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Extreme
Check with supervisor for appropriate personal protection in accordance with rating.

DISCLAIMER:

The information contained herein relates only to the specific material identified. Flexabar Corporation believes that the information is accurate and reliable as of the preparation date of this material safety data sheet, but no representation, guarantee or warranty expressed or implied is made as to the accuracy, reliability or completeness of the information. Flexabar Corporation urges persons receiving this information to make their own determination as to the information's suitability and completeness for their particular application.